

We are Quality Manufacturers of :

- All types & Sizes of Expansion Joints & Bellows.
- All types & Sizes of Rubber Sheets & Matting.
- Electrical Rubber Insulated Sheets of IS & BS Standards.
- All types of customized Moulded & Extruded Products.
- Pharmaceuticals Products.
- All types of Gasket & Diaphragms.



Kiran
Rubber
Industries

135, Shiv-Krupa Industrial Estate,
LBS Road, Opp. Raj Legacy,
Vikhroli (W), Mumbai 400 083.

Tel. : +91 (0) 22 4263-7400

Fax : +91 (0) 22 4263-7499

E-Mail : info@kiranrubber.com

Website : www.kiranrubber.com

KRUBBER - ADHESIVE

Material Specifications

Base	Synthetic Rubber
Application	Fixing of KRUBBER PROTEKT sheets to cement, concrete, metal, wood etc.
Solvent	Aliphatic and Aromatic solvent combination
Viscosity	2200 ± 100 cps at 30°± 5°C.

Application Process

Make sure that the surfaces to be bonded are even, clean, dry and free from grease/oil. A thin coat of adhesive is to be applied uniformly on both the surfaces to be joined. Porous substrates may require double coat for superior bonding. Allow 8-10 minutes for solvent evaporation. Press the surfaces firmly after bonding together. Final strength is to be achieved after 24 hrs.

Caution

Replace lid immediately after partial use. Store in a cool and dry place. Highly Inflammable. Keep away from Hot Surfaces.

Packing Size

5 Ltrs and 20 Ltrs